



# Quadra Video Quality Report

QUADRA RELEASE 5.7.0

## Table of Contents

1.	Document Outline.....	1
2.	Evaluation Results.....	2
2.1.	High Quality Dual Pass Configuration.....	3
2.1.1.	High Quality Dual Pass Results.....	4
2.2.	Low Delay Configuration .....	6
2.2.1.	Low Delay Results .....	7
2.3.	High Quality Dual Pass Configuration Capped CRF.....	9
2.3.1.	High Quality Dual Pass Capped CRF Results .....	10
3.	Appendix .....	11
3.1.	Video Sequences .....	11
4.	Legal Notice.....	13

## 1. Document Outline

This document presents the quality evaluation results for NETINT's family of Quadra products.

Quadra is evaluated using various settings in AcoPVC, HEVC, and AV1 codecs. The results are compared against x264 and x265, Nvidia's H.264 and H.265 hardware encoder, and the SVT-AV1 software encoder, these being used as anchors. Target bit rates in these tests were 1, 3, 5, 7 and 10 Mbps.

## 2. Evaluation Results

The quality performance of Quadra uses the following datasets:

- **NETINT's QuadraBringUpFILM dataset**
  - YUV 4:2:0 sequences
  - Resolution: 1080p
  - Frame rate: 25 and 50 FPS
- **NETINT's VITS2021SmallSet:**
  - YUV 4:2:0 sequences
  - Resolution: 2160p
  - Frame rate: 30 and 60 FPS
- **NETINT's QuadraBringUpCGI:**
  - YUV 4:2:0 sequences
  - Resolution: 1080p
  - Frame rate: 60 FPS
- **NETINT's QuadraSimpleGaming:**
  - YUV 4:2:0 sequences
  - Resolution: 720p
  - Frame rate: 60 FPS

Quadra is evaluated using x264, x265, SVT-AV1, and FFmpeg with dual pass and low latency configurations. To help replicate these results and for references, the following versions are used:

- x264: Version 0.152.2854 e9a5903
- x265: Version 3.5+1-f0c1022b6
- FFmpeg: Version 4.3.1-static
- SVT-AV1 v1.2
- NVIDIA-SMI 515.65.01, Driver Version: 515.65.01, CUDA Version: 11.7

## 2.1. High Quality Dual Pass Configuration

Dual pass configuration uses QuadraBringUpFILM and VITS2021SmaSet datasets. Anchors are created with the following commands:

- **x264/x265**  
*x264 --tune psnr --aq-mode 0 --no-scenecut --bframes 3 --b-adapt 0 --rc-lookahead 16 --input-res 1920x1080 --fps 50.0 --bitrate 5833 --vbv-buFSIZE 11666 --keyint 100 --min-keyint 100 --preset fast --frames 500 -o [path to output file] [path to source file]*
- **Nvidia**  
*ffmpeg\_nvidia -y -vsync 0 -hwaccel cuda -s:v 1920x1080 -r 25.0 -i [path to source file] -c:v h264\_nvenc -pix\_fmt yuv420p -preset p4 -rc cbr -bufsize [buffer size] -tune hq -bf 3 -b\_ref\_mode middle -b\_adapt 0 -rc-lookahead 15 -vsync 0 -b\_qfactor 1 -spatial-aq 0 -temporal-aq 0 -b:v 32708333 -maxrate 32708333 -minrate 32708333 -profile:v high -g 50.0 -spatial-aq 0 -temporal-aq 1 -vsync 0 -vframes 690 [path to output file]*  
  
NOTE - *buffer size* varies depending on the bitrate:  $\text{buffer size} = (2 * \text{bitrate} / 1000)K$
- **SVT-AV1**  
*SvtAv1EncApp --rc 1 --preset 10 --keyint 50 -w 1920 -h 1080 --tbr 32708 --lookahead 16 --passes 2 --lp 1 --fps 25.0 -n 690 -b [path to output file] -i [path to source file]*

Sequences used to compare to the anchors are generated using the following commands:

- **RDOQ enabled**  
*FFmpeg -y -vsync 0 -s 3840x2160 -r 60.0 -i [path to source file] -c:v av1\_ni\_quadra\_enc -xcodec-params level=0:frameRate=60:RcEnable=1:vbvBufferSize=2000:bitrate=8000000:intraPeriod=120:gopPresetIdx=-1:entropyCodingMode=1:lookaheadDepth=16:cuLevelRCEnable=0:rdoLevel=3:EnableRdoQuant=1 -vframes 600 [path to output file]*
- **RDOQ disabled**  
*FFmpeg -y -vsync 0 -s 3840x2160 -r 60.0 -i [path to source file] -c:v av1\_ni\_quadra\_enc -xcodec-params level=0:frameRate=60:RcEnable=1:vbvBufferSize=2000:bitrate=8000000:intraPeriod=120:gopPresetIdx=-1:entropyCodingMode=1:lookaheadDepth=16:cuLevelRCEnable=0:rdoLevel=3:EnableRdoQuant=0 -vframes 600 [path to output file]*

## 2.1.1. High Quality Dual Pass Results

Quadra H.264 compared against x264 presets and Nvidia H.264.

Quadra H.265 compared against x265 presets and Nvidia H.265.

Quadra AV1 compared against x265 presets and SVT AV1 Preset 10 and 12.

High Quality Dual Pass test uses QuadraBringUpFILM and VITS2021SmallSet datasets configured with RDOQ enabled and RDOQ disabled. For more information on the RDOLevel and RDOQ please refer to the **Integration Programming Guide** provided inside the Quadra release package.

H.264 RDO levels are not shown as all levels provides the same values.

H.265 RDO level set to 1, 2, and 3.

AV1 RDO level set to 1, 2, and 3 with RDOQ disabled.

The tables below show the Quadra encoder output compared against the presets, Nvidia, and SVT AV1 Presets.

PSNR BD Rate Savings %	RDOQ	RDO Level	ultrafast	superfast	veryfast	faster	fast	medium	slow	slower	veryslow	Nvidia	SVT AV1 Preset 10	SVT AV1 Preset 12
Quadra AVC	0	-	-58.74	-23.8	-17.2	2.27	7.45	2.74	7.88	28.5	30.05	-8.97		
Quadra AVC	1	-	-61.48	-28.94	-22.77	-4.68	0.08	-4.01	0.82	19.48	20.93	-15.12		
Quadra HEVC	0	1	-27.72	-21.86	-0.05	-0.04	3.9	9.72	25.65	33.43	36.42	-8.1		
Quadra HEVC	0	2	-31.73	-26.13	-5.44	-5.42	-1.66	3.82	18.92	26.31	29.12	-12.97		
Quadra HEVC	0	3	-33.77	-28.31	-8.25	-8.24	-4.58	0.75	15.38	22.57	25.3	-15.46		
Quadra HEVC	1	1	-32.07	-26.47	-5.37	-5.36	-1.56	3.76	18.8	26.25	29.03	-13.07		
Quadra HEVC	1	2	-36.03	-30.64	-10.59	-10.58	-6.87	-1.9	12.51	19.6	22.23	-17.88		
Quadra HEVC	1	3	-38	-32.74	-13.33	-13.31	-9.74	-4.89	9	15.83	18.36	-20.28		
Quadra AV1	0	1	-27.9	-21.94	0.11	0.13	4.19	9.79	25.66	33.46	36.42		5.44	-11.58
Quadra AV1	0	2	-31.19	-25.54	-4.78	-4.76	-0.96	4.35	19.27	26.65	29.42		0.03	-16.03
Quadra AV1	0	3	-33.21	-27.67	-7.6	-7.58	-3.87	1.29	15.79	22.95	25.63		-3.22	-18.65

**Table 1:** High Quality Dual Pass - Average PSNR BD Rate Savings (in percent) for VITS2021SmallSet dataset

PSNR BD Rate Savings %	RDOQ	RDO Level	ultrafast	superfast	veryfast	faster	fast	medium	slow	slower	veryslow	Nvidia	SVT Av1 Preset 10	SVT Av1 Preset 12
Quadra AVC	0	-	-53.6	-20.55	-15.42	0.05	4.13	7.54	12.54	18.59	19.98	-3.71		
Quadra AVC	1	-	-55.99	-24.56	-19.69	-4.94	-1.11	2.08	6.82	12.39	13.7	-8.66		
Quadra HEVC	0	1	-18.26	-10.66	-0.57	-0.48	6.33	7.02	21.16	27.97	30.9	-2.88		
Quadra HEVC	0	2	-22.48	-15.15	-5.5	-5.42	1.07	1.72	15.12	21.53	24.27	-7.53		
Quadra HEVC	0	3	-24.27	-17.03	-7.56	-7.48	-1.08	-0.49	12.67	18.95	21.63	-9.48		
Quadra HEVC	1	1	-22.35	-14.91	-5.1	-5.02	1.67	2.26	16.04	22.5	25.34	-7.16		
Quadra HEVC	1	2	-26.55	-19.42	-10.05	-9.97	-3.63	-3.08	9.88	15.95	18.61	-11.84		
Quadra HEVC	1	3	-28.35	-21.31	-12.12	-12.05	-5.8	-5.3	7.4	13.33	15.93	-13.79		
Quadra AV1	0	1	-17.15	-9.46	0.65	0.75	7.62	8.33	22.64	29.36	32.29		11.07	-6.6
Quadra AV1	0	2	-20.84	-13.47	-3.85	-3.77	2.72	3.4	16.87	23.17	25.91		5.9	-10.78
Quadra AV1	0	3	-22.82	-15.54	-6.14	-6.06	0.32	0.94	14.11	20.25	22.92		3.38	-12.97

**Table 2:** High Quality Dual Pass - Average PSNR BD Rate Savings (in percent) for QuadraBringUpFILM dataset

## 2.2. Low Delay Configuration

Low delay (low latency) configuration uses QuadraBringUpCGI (gaming sequences) and QuadraSimpleGaming datasets. Anchors are created using the following commands:

- **x264/x265**  
*x264 --tune zerolatency --aq-mode 0 --no-psy --no-scenecut --input-res 1920x1080 --fps 30.0 --bitrate 7000 --vbv-buFSIZE 14000 --keyint 60 --min-keyint 60 --preset fast --frames 650 -o [path to output file] [path to source file]*
- **Nvidia**  
*FFmpeg\_nvidia -y -s:v 1920x1080 -r 60.0 -i [path to source file] -c:v hevc\_nvenc -pix\_fmt yuv420p -preset p4 -zerolatency 1 -b\_adapt 0 -bf 0 -vsync 0 -rc-lookahead 0 -spatial-aq 0 -temporal-aq 0 -rc cbr -tune ull -bufsize [buffer size] -b:v 1000000 -maxrate 1000000 -minrate 1000000 -profile:v main -g 120.0 -vsync 0 -vframes 252 [path to output file]*

NOTE - buffer size varies depending on the bitrate:  $\text{buffer size} = (2 * \text{bitrate} / 1000)K$

- **SVT-AV1**  
*SvtAv1EncApp --rc 1 --preset 10 --keyint 120 -w 1920 -h 1080 --tbr 7500 --mbr 7550 --pred-struct 2 --lp 1 --fps 60.0 -n 400 -b [path to output file] -i [path to source file]*

Sequences used to compare to the anchors are generated using the following commands:

- **RDOQ enabled**  
*FFmpeg -y -vsync 0 -s 1920x1080 -r 60.0 -i [path to source file] -c:v h264\_ni\_quadra\_enc -xcoder-params level=0:frameRate=60:RcEnable=1:vbvBufferSize=2000:bitrate=1000000:intraPeriod=120:gopPresetIdx=3:entropyCodingMode=1:lookaheadDepth=0:cuLevelRCEnable=1:rdoLevel=3:tolCtbRcInter=0:tolCtbRcIntra=0:EnableRdoQuant=1 -vframes 400 [path to output file]*
- **RDOQ disabled**  
*FFmpeg -y -vsync 0 -s 1920x1080 -r 60.0 -i [path to source file] -c:v h264\_ni\_quadra\_enc -xcoder-params level=0:frameRate=60:RcEnable=1:vbvBufferSize=2000:bitrate=1000000:intraPeriod=120:gopPresetIdx=3:entropyCodingMode=1:lookaheadDepth=0:cuLevelRCEnable=1:rdoLevel=3:tolCtbRcInter=0:tolCtbRcIntra=0:EnableRdoQuant=0 -vframes 400 [path to output file]*



### 2.2.1. Low Delay Results

Quadra H.264 compared against x264 presets and Nvidia H.264.

Quadra H.265 compared against x265 presets and Nvidia H.265.

Quadra AV1 compared against x265 presets and SVT AV1 Preset 10 and 12.

Low Delay test uses QuadraBringUpCGI and QuadraSimpleGaming datasets configured with RDOQ enabled and RDOQ disabled. For more information on the RDOLevel and RDOQ please refer to the **Integration Programming Guide** provided inside the Quadra release package.

H.264 RDO levels are not shown as all levels provides the same values.

H.265 RDO level set to 1, 2, and 3.

AV1 RDO level set to 1, 2, and 3 with RDOQ disabled.

The tables below show the Quadra encoder output compared against the presets, Nvidia, and SVT AV1 Presets.

PSNR BD Rate Savings %	RDOQ	RDO Level	ultrafast	superfast	veryfast	faster	fast	medium	slow	slower	veryslow	Nvidia	SVT AV1 Preset 10	SVT AV1 Preset 12
Quadra AVC	0	-	-45.59	-13.86	-10.01	4.95	12.73	2.97	7.4	21.55	22.11	6.92		
Quadra AVC	1	-	-48.7	-18.36	-14.66	-0.48	6.92	-2.18	2.03	15.21	15.75	2.03		
Quadra HEVC	0	1	-34.95	-23.95	-12.38	-12.37	-9.68	-7.51	4.02	11.26	14.49	-6.78		
Quadra HEVC	0	2	-37.36	-26.69	-15.52	-15.51	-12.91	-10.78	0.3	7.28	10.38	-10.12		
Quadra HEVC	0	3	-38.05	-27.47	-16.41	-16.4	-13.83	-11.7	-0.73	6.17	9.25	-11.05		
Quadra HEVC	1	1	-37.85	-27.17	-15.8	-15.8	-13.17	-10.87	0.22	7.22	10.33	-9.9		
Quadra HEVC	1	2	-40.09	-29.74	-18.74	-18.75	-16.21	-13.96	-3.27	3.43	6.4	-13.08		
Quadra HEVC	1	3	-40.75	-30.47	-19.58	-19.58	-17.08	-14.83	-4.25	2.39	5.34	-13.99		
Quadra AV1	0	1	-27.92	-16.41	-3.98	-3.99	-1.06	1.26	12.96	20.27	23.45		-3.82	-26.49
Quadra AV1	0	2	-29.36	-18.2	-6.06	-6.07	-3.22	-0.92	10.44	17.38	20.43		-6.59	-28.64
Quadra AV1	0	3	-29.84	-18.74	-6.69	-6.7	-3.87	-1.59	9.65	16.52	19.52		-7.4	-29.25

**Table 3:** Low Delay - Average PSNR BD Rate Savings (in percent) for QuadraBringUpCGI dataset

PSNR BD Rate Savings %	RDOQ	RDO Level	ultrafast	superfast	veryfast	faster	fast	medium	slow	slower	veryslow	Nvidia	SVT Av1 Preset 10	SVT Av1 Preset 12
Quadra AVC	0	-	-38.9	-18.5	-17.02	-14.71	-1.74	-1.29	3.67	4.11	6.95	8.12		
Quadra AVC	1	-	-44.39	-24.93	-23.41	-21.22	-9.09	-8.68	-4.11	-3.74	-1.12	1.32		
Quadra HEVC	0	1	-32.76	-18.05	-8.43	-8.28	-5.5	-6.33	5.74	9.31	12.12	-12.25		
Quadra HEVC	0	2	-37.35	-23.25	-14.15	-14	-11.41	-12.2	-0.84	2.51	5.15	-17.55		
Quadra HEVC	0	3	-38.97	-25.06	-16.13	-15.99	-13.48	-14.24	-3.16	0.1	2.68	-19.37		
Quadra HEVC	1	1	-37.68	-23.16	-13.84	-13.69	-11	-11.83	-0.14	3.33	6.06	-17.22		
Quadra HEVC	1	2	-41.42	-27.43	-18.58	-18.44	-15.9	-16.7	-5.7	-2.44	0.12	-21.58		
Quadra HEVC	1	3	-42.78	-28.98	-20.31	-20.17	-17.68	-18.47	-7.72	-4.54	-2.03	-23.17		
Quadra AV1	0	1	-23.32	-7.09	3.53	3.7	6.74	5.81	18.94	22.76	25.79		26.61	1.13
Quadra AV1	0	2	-25.83	-10.22	-0.03	0.14	3.04	2.15	14.74	18.36	21.26		22.51	-2.18
Quadra AV1	0	3	-26.92	-11.59	-1.62	-1.45	1.37	0.52	12.86	16.39	19.23		20.65	-3.53

**Table 4:** Low Delay - Average PSNR BD Rate Savings (in percent) for QuadraSimpleGaming dataset

## 2.3. High Quality Dual Pass Configuration Capped CRF

Dual pass configuration uses QuadraBringUpFILM dataset. Anchors are created using the following commands:

- **x264**  
*FFmpeg -psnr -i [path to source file] -c:v libx264 -preset medium -x264-params "keyint=120:bframes=3:log-level=full:crf=19:rc-lookahead=10:vbv-maxrate=6000:vbv-buFSIZE=6000" [path to output file]*
- **x265**  
*FFmpeg -psnr -i [path to source file] -c:v libx265 -preset medium -x265-params "keyint=120:bframes=3:log-level=full:crf=19:rc-lookahead=10:vbv-maxrate=6000:vbv-buFSIZE=6000" [path to output file]*

Sequences used are generated using the following commands:

- **RDOQ enabled**  
*FFmpeg -y -vsync 0 -s 3840x2160 -r 60.0 -i [path to source file] -c:v av1\_ni\_quadra\_enc -xcoder-params gopPresetIdx=5:RcEnable=0:crf=19:intraPeriod=120:lookAheadDepth=10:EnableRdoQuant=1:rdoLevel=1:cuLevelRCEnable=1:vbvBufferSize=1000:bitrate=6000000:tolCtbRcInter=0:tolCtbRcIntra=0:zeroCopyMode=0 -vframes 600 [path to output file]*
- **RDOQ disabled**  
*FFmpeg -y -vsync 0 -s 3840x2160 -r 60.0 -i [path to source file] -c:v av1\_ni\_quadra\_enc -xcoder-params gopPresetIdx=5:RcEnable=0:crf=19:intraPeriod=120:lookAheadDepth=10:EnableRdoQuant=0:rdoLevel=1:cuLevelRCEnable=1:vbvBufferSize=1000:bitrate=6000000:tolCtbRcInter=0:tolCtbRcIntra=0:zeroCopyMode=0 -vframes 600 [path to output file]*

### 2.3.1. High Quality Dual Pass Capped CRF Results

Quadra H.264 compared against x264 medium preset.

Quadra H.265 compared against x265 medium preset.

High Quality Dual Pass test uses QuadraBringUpFILM dataset configured with RDOQ enabled and RDOQ disabled. For more information on the RDOLevel and RDOQ please refer to the **Integration Programming Guide** provided inside the Quadra release package.

The encoder displays competitive performance in several key areas. The gains show Quadra delivering consistent video quality across different scenes, irrespective of their complexity. This consistent quality underscores our encoder's robustness, ensuring viewers get a dependable visual experience.

H.264 RDO levels are not shown as all levels provides the same values.

H.265 RDO level set to 1, 2, and 3.

AV1 RDO level set to 1, 2, and 3 with RDOQ disabled.

The tables below show the Quadra encoder output.

PSNR BD Rate Savings %	RDOQ	RDO Level	medium
Quadra AVC	0	-	-7.41
Quadra AVC	1	-	-7.98
Quadra HEVC	0	1	-3.78
Quadra HEVC	0	2	-7.91
Quadra HEVC	0	3	-9.55
Quadra HEVC	1	1	-5.97
Quadra HEVC	1	2	-7.69
Quadra HEVC	1	3	-9.35
Quadra AV1	0	1	-3.78
Quadra AV1	0	2	-7.51
Quadra AV1	0	3	-9.2

**Table 5:** High Quality Dual Pass Capped CRF - Average PSNR BD Rate Savings (in percent) for QuadraBringUpFILM dataset

### 3. Appendix

#### 3.1. Video Sequences

This section will list the video sequences in the datasets used for this report. These sequences are taken from YouTube UGC Dataset (<https://media.withyoutube.com>) and Derf's collection (<https://media.xiph.org/video/derf>).

##### **QuadraBringUpFILM Dataset:**

blue\_sky\_1920x1080p25\_420  
crowd\_run\_1920x1080p50\_420  
ducks\_take\_off\_1920x1080p50\_420  
in\_to\_tree\_1920x1080p50\_420  
old\_town\_cross\_1920x1080p50\_420  
park\_joy\_1920x1080p50\_420  
pedestrian\_area\_1920x1080p25\_420  
riverbed\_1920x1080p25\_420  
rush\_hour\_1920x1080p25\_420  
station2\_1920x1080p25\_420  
sunflower\_1920x1080p25\_420  
tractor\_1920x1080p25\_420

##### **VITS2021SmallSet Dataset:**

construction\_field\_3840x2160\_p30\_420  
fountains\_3840x2160\_p30\_420  
marathon\_3840x2160\_p30\_420  
tall\_buildings\_3840x2160\_p30\_420  
Bosphorus\_3840x2160p60\_420  
Fortnite\_4k\_1\_3840x2160p60\_420  
Jockey\_3840x2160p60\_420  
ShakeNDry\_3840x2160p60\_420

##### **QuadraBringUpCGI Dataset:**

CSGO\_cut\_280\_879\_1920x1080p60\_420  
DOTA2\_cut\_1735\_2285\_1920x1080p60\_420  
EuroTruckSimulator2\_cut\_500\_993\_1920x1080p60\_420  
Gaming\_1080P-6530\_1920x1080p60\_420  
Gaming\_1080P-72c8\_1920x1080p60\_420  
Gaming\_1080P-7a1e\_1920x1080p60\_420  
GTAV\_cut\_1104\_1403\_1920x1080p60\_420  
GTAV\_cut\_2700\_2999\_1920x1080p60\_420  
WITCHER3\_cut\_2334\_2585\_1920x1080p60\_420  
WITCHER3\_cut\_450\_849\_1920x1080p60\_420

**QuadraSimpleGaming Dataset:**

Amongus-01a1\_1280x720p30\_420  
Amongus-02b2\_1280x720p30\_420  
Biped-01c1\_1280x720p30\_420  
Biped-03c3\_1280x720p30\_420  
Biped-05c5\_1280x720p30\_420  
Genshin-04e4\_1280x720p30\_420  
Genshin-02f2\_1280x720p30\_420  
RAFT-01h3\_1280x720p30\_420  
Runescape-05g5\_1280x720p30\_420  
Runescape-06g9\_1280x720p30\_420  
Stumble-7ae5\_1280x720p30\_420  
Stumble-7bg2\_1280x720p30\_420

## 4. Legal Notice

Information in this document is provided in connection with NETINT products. No license, express or implied, by estoppel or otherwise, to any intellectual property rights is granted by this document. Except as provided in NETINT's terms and conditions of sale for such products, NETINT assumes no liability whatsoever and NETINT disclaims any express or implied warranty, relating to sale and/or use of NETINT products including liability or warranties relating to fitness for a particular purpose, merchantability, or infringement of any patent, copyright or other intellectual property right.

A "Mission Critical Application" is any application in which failure of the NETINT Product could result, directly or indirectly, in personal injury or death. Should you purchase or use NETINT's products for any such mission critical application, you shall indemnify and hold NETINT and its subsidiaries, subcontractors and affiliates, and the directors, officers, and employees of each, harmless against all claims costs, damages, and expenses and reasonable attorney's fees arising out of, directly or indirectly, any claim of product liability, personal injury, or death arising in any way out of such mission critical application, whether or not NETINT or its subcontractor was negligent in the design, manufacture, or warning of the NETINT product or any of its parts.

NETINT may make changes to specifications, technical documentation, and product descriptions at any time, without notice. The information here is subject to change without notice. Do not finalize a design with this information. The products described in this document may contain design defects or errors known as errata which may cause the product to deviate from published specifications.

NETINT, Codensity, and NETINT Logo are trademarks of NETINT Technologies Inc. All other trademarks or registered trademarks are the property of their respective owners.

© 2026 NETINT Technologies Inc. All rights reserved.